# Arize®



CUSTOMER NAME	
PROJECT NAME	
DATE	TYPE
CATALOG NUMBER	

# Arize Element® L400

#### HORT138

#### **Greenhouses and Indoor Farms**

The Arize Element L400 top light is an LED growing system for photoperiod extension or low DLI crops. The compact Element L400 delivers up to 550  $\mu$ mol/s with minimal shadowing, and radiates negligible heat compared to an HPS or CMH system, for year-round growing.

#### **Optical System**

Efficacy Range:	2.7 - 2.8µmol/J
Spectrums:	PPR, PPB

#### **Ambient Temperature**

ТҮРЕ	TEMPERATURE RATING
Operating Temperature	0°C to +40°C (32°F to 104°F)

### Electrical

IP Rating IP66 & UL wet rated

#### **Rated Lifetime**

36,000 hour L90 per TM-21

#### Features

Low weight and novel installation method simplifies the mounting process

Modular design allows for the power supply to be mounted remotely, away from the fixture

Unique design and small footprint minimize shadowing, allowing more natural light through

Negligible heat radiation compared to HPS or CMH fixtures

Impact-resistant design made of polycarbonate and aluminum

# **Certifications & Warranty**

Five-year system warranty

Current



CUSTOMER NAME


DATE

**PROJECT NAME** 

CATALOG NUMBER

TYPE


L400



# Spectra

#### Type R

High red light to optimize plant growth and photosynthesis



#### Туре В

Light that supports biomass and secondary metabolite production



360 380 400 420 440 460 480 500 520 540 560 580 600 620 640 660 680 700 720 740 760 780 800 Wavelength (nm)

SPECTRUM PHOTON DISTRIBUTION				
Ratio	Blue PF	Green PF	Red PF	Far Red PF
PPR	10.0%	0.0%	90.0%	0.0%
PPB	20.0%	0.0%	80.0%	0.0%

# **Product Information**

SKU	DESCRIPTION	SPECTRUM	ELECTRICAL POWER (W)	PPF (µMOL/S)	EFFICACY (µMOL/J)	PACKAGE QUANTITY
93067254	GEHR3007M-N120CH-PPR-1	PPR	195	550	2.8	4pcs / box
	GEPSC070-210G-ADFNA					
93067255	GEHR3007MN120CH-PPB-1	PPB	195	525	2.7	4pcs / box
	GEPSC070-210G-ADFNA					

# **Accessories**

SKU	DESCRIPTION	LONG DESCRIPTION	PACKAGE QUANTITY
93038986	GEPSC070-210G-ADFNA	120V-240VAC, 700mA, 210W Driver, UL	1pc
93067607	GECA30A14-AA06B	6 foot (1.83 m) inter-connection cable, UL	32pcs / box
93 067608	GECA30A14-AA12B	12 foot (3.66 m) inter-connection cable, UL	16pcs / box

